Specifications

- Bench mounted cut-off machine.
- Robustly built in sheet steel.
- The hood opens completely to provide easy access and includes safety switch.
- Two quick clamping vices,
 2 positions: Horizontal or Vertical.
- Cutting wheel diameter 250 or 300 mm
- 2 rotational speed of the cutting wheel: 3200 and 3800 rpm.
- Motor 3 HP voltages available 230V single-phase.
- Lighting.
- 2 adjustable jets mounted on each side of the wheel.
- PVC pump and tank.
- Built in accordance with EEC standards.

AUTOMATIC MODULE

- Continuously adjustable variable feed speed from 0 to 160 mm/mn.
- Cut by impulses.
- Quick advance and return.
- Automatic module can be disengaged for manual cutting.
- Automatic return after end of cutting, with cut-off wheel rotation stop.



T255/300 Automatic.



Clamping vice in vertical position.

MECATOME T 255/300



MECATOME T255/300 is a sensitive manual cut-off machine

• Motor and cutting wheel (250 or 300 mm diameter) are mounted on a free running bearing which allows, thanks to the arm movement, a clean and precise cut.

• The quick clamping vices operate in both horizontal and vertical positions.

• Due to its automatic module, the MECAPOL T255/300 offers automatic cutting functions, with adjustable variable feed speed, return and stop after end of cutting, allowing the operator to return to the machine after the cut is complete. The automatic functions can be disengaged allowing a manual cutting operation when required for special applications.

38320 Brié et Angonnes - Grenoble - France. Tél. : E-mail : presi@presi.com



Cutting capacity

Ø 250 mm	Ø 300 mm
Ø 75 mm	Ø 95 mm
65 x 65 mm	85 x 85 mm
95 x 50 mm 120 x 25 mm	120 x 60 mm 150 x 25 mm



Base cabinet

Accessories

- Automatic module variable speed for feeding advance pulse cutting system
- Base cabinet
- Cleaning set

TECNIMETAL

IGNACIO ELLACURÍA, 10-12 TELS. 91 356 22 94 - FAX: 91 355 58 08 28017 MADRID